

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: March 23, 2004

In the Claims:

1. (Currently amended) A cryptographic device comprising:

a cryptographic module and a communications module coupled thereto;

said cryptographic module comprising a user network interface, a host network processor coupled to said user network interface, and a cryptographic processor coupled to said host network processor;

said communications module comprising a network communications interface coupled to said cryptographic processor;

said host network processor generating cryptographic processor command packets for said cryptographic processor each comprising an address portion and a data portion, and encapsulating command packets for said communications module in the data portions of said cryptographic processor command packets;

said cryptographic processor passing the communications module command packets to said communications module without performing cryptographic processing thereon.

2. (Original) The cryptographic device of Claim 1 wherein said host network processor formats the data portions based upon the simple network management protocol (SNMP).

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: **March 23, 2004**

3. (Original) The cryptographic device of Claim 1 wherein the communications module command packets comprise Ethernet packets.

4. (Original) The cryptographic device of Claim 1 wherein the cryptographic processor command packets comprise Internet protocol (IP) packets.

5. (Original) The cryptographic device of Claim 1 wherein said cryptographic module further comprises:

a first housing carrying said user network interface, said host network processor, and said cryptographic processor; and

a first connector carried by said first housing and coupled to said cryptographic processor.

6. (Original) The cryptographic device of Claim 5 wherein said communications module further comprises:

a second housing carrying said network communications interface; and

a second connector carried by said second housing and being removably mateable with said first connector of said cryptographic module.

7. (Original) The cryptographic device of Claim 1 wherein said cryptographic processor comprises:

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: **March 23, 2004**

an unencrypted data buffer circuit coupled to said host network processor;

a cryptography circuit coupled to said unencrypted data buffer circuit; and

an encrypted data buffer circuit coupled to said cryptography circuit.

8. (Original) The cryptographic device of Claim 1 wherein said communications module comprises a predetermined one from among a plurality of interchangeable communications modules each for communicating over a different communications media.

9. (Original) The cryptographic device of Claim 1 wherein said network communications interface comprises at least one of a wireless LAN (WLAN) communication circuit, a wireline communication circuit, and a fiber optic communication circuit.

10. (Original) The cryptographic device of Claim 1 wherein said user network interface comprises an Ethernet Local Area Network (LAN) interface, and wherein said network communications interface comprises a network LAN interface.

11. (Currently amended) The cryptographic device of Claim ~~4~~ 5 wherein said cryptographic module further comprises a tamper circuit for disabling said cryptographic processor based upon tampering with said first housing.

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: **March 23, 2004**

12. (Currently amended) A cryptographic device comprising:

a cryptographic module and a communications module coupled thereto;

said cryptographic module comprising a user Local Area Network (LAN) interface, a host network processor coupled to said user LAN interface, and a cryptographic processor coupled to said host network processor;

said communications module comprising a network LAN interface coupled to said cryptographic processor;

said host network processor generating cryptographic processor command packets for said cryptographic processor each comprising an address portion and a data portion, and encapsulating Ethernet command packets for said communications module in the data portions of said cryptographic processor command packets, said host network processor formatting the data portions based upon the simple network management protocol (SNMP);

said cryptographic processor passing the communications module command packets to said communications module without performing cryptographic processing thereon.

13. (Original) The cryptographic device of Claim 12 wherein the cryptographic processor command packets comprise Internet protocol (IP) packets.

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: **March 23, 2004**

14. (Original) The cryptographic device of Claim 12 wherein said cryptographic module further comprises:

a first housing carrying said user LAN interface, said host network processor, and said cryptographic processor; and

a first connector carried by said first housing and coupled to said cryptographic processor.

15. (Original) The cryptographic device of Claim 14 wherein said communications module further comprises:

a second housing carrying said network LAN interface; and

a second connector carried by said second housing and being removably mateable with said first connector of said cryptographic module.

16. (Original) The cryptographic device of Claim 12 wherein said cryptographic processor comprises:

an unencrypted data buffer circuit coupled to said host network processor;

a cryptography circuit coupled to said unencrypted data buffer circuit; and

an encrypted data buffer circuit coupled to said cryptography circuit.

17. (Original) The cryptographic device of Claim 12 wherein said communications module comprises a predetermined one

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: **March 23, 2004**

from among a plurality of interchangeable communications modules each for communicating over a different communications media.

18. (Original) The cryptographic device of Claim 12 wherein said network LAN interface comprises at least one of a wireless LAN (WLAN) communication circuit, a wireline LAN communication circuit, and a fiber optic LAN communication circuit.

19. (Original) The cryptographic device of Claim 12 wherein said user LAN interface comprises an Ethernet interface.

20. (Original) The cryptographic device of Claim 12 wherein said cryptographic module further comprises a tamper circuit for disabling said cryptographic processor based upon tampering with said first housing.

21. (Currently amended) A communications method comprising:

coupling a cryptographic module to a network device, the cryptographic module comprising a user network interface, a host network processor coupled to the user network interface, and a cryptographic processor coupled to the host network processor;

providing a communications module comprising a network communications interface coupled to the cryptographic processor;

causing the host network processor to generate cryptographic processor command packets for the cryptographic

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: **March 23, 2004**

processor each comprising an address portion and a data portion, and to encapsulate command packets for the communications module in the data portions of the cryptographic processor command packets; and

causing the cryptographic processor to pass the communications module command packets to the communications module without performing cryptographic processing thereon.

22. (Original) The method of Claim 21 further comprising causing the host network processor to format the data portions based upon the simple network management protocol (SNMP).

23. (Original) The method of Claim 21 wherein the communications module command packets comprise Ethernet packets.

24. (Original) The method of Claim 21 wherein the cryptographic processor command packets comprise Internet protocol (IP) packets.

25. (Original) The method of Claim 21 wherein the user network interface comprises an Ethernet Local Area Network (LAN) interface, and wherein the network communications interface comprises a network LAN interface.

26. (Currently amended) A communications system comprising:

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: March 23, 2004

a plurality of network devices coupled together to define a network, and a cryptographic device coupled to at least one of said network devices;

said cryptographic device comprising a cryptographic module coupled to said at least one network device, and a communications module coupled to said cryptographic module;

said cryptographic module comprising a user network interface, a host network processor coupled to said user network interface, and a cryptographic processor coupled to said host network processor;

said communications module comprising a network communications interface coupled to said cryptographic processor;

said host network processor generating cryptographic processor command packets for said cryptographic processor each comprising an address portion and a data portion, and encapsulating command packets for said communications module in the data portions of said cryptographic processor command packets;

said cryptographic processor passing the communications module command packets to said communications module without performing cryptographic processing thereon.

27. (Original) The system of Claim 26 wherein said host network processor formats the data portions based upon the simple network management protocol (SNMP).

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: March 23, 2004

28. (Original) The system of Claim 26 wherein the communications module command packets comprise Ethernet packets, and wherein the cryptographic processor command packets comprise Internet protocol (IP) packets.

29. (Original) The system of Claim 26 wherein said cryptographic module further comprises:

a first housing carrying said user network interface, said host network processor, and said cryptographic processor; and

a first connector carried by said first housing and coupled to said cryptographic processor.

30. (Original) The system of Claim 29 wherein said communications module further comprises:

a second housing carrying said network communications interface; and

a second connector carried by said second housing and being removably mateable with said first connector of said cryptographic module.

31. (Original) The system of Claim 26 wherein said cryptographic processor comprises:

an unencrypted data buffer circuit coupled to said host network processor;

a cryptography circuit coupled to said unencrypted data buffer circuit; and

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: **March 23, 2004**

an encrypted data buffer circuit coupled to said cryptography circuit.

32. (Original) The system of Claim 26 wherein said communications module comprises a predetermined one from among a plurality of interchangeable communications modules each for communicating over a different communications media.

33. (Original) The system of Claim 26 wherein said network communications interface comprises at least one of a wireless LAN (WLAN) communication circuit, a wireline communication circuit, and a fiber optic communication circuit.

34. (Original) The system of Claim 26 wherein said user network interface comprises an Ethernet Local Area Network (LAN) interface, and wherein said network communications interface comprises a network LAN interface.

35. (Original) The system of Claim 26 wherein said cryptographic module further comprises a tamper circuit for disabling said cryptographic processor based upon tampering with said first housing.

36. (New) A cryptographic module comprising:
a user network interface;
a host network processor coupled to said user network interface; and

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: **March 23, 2004**

a cryptographic processor coupled to said host network processor;

said host network processor generating cryptographic processor command packets for said cryptographic processor each comprising an address portion and a data portion, and encapsulating command packets for a network communications module in the data portions of said cryptographic processor command packets;

said cryptographic processor passing the communications module command packets to the network communications module without performing cryptographic processing thereon.

37. (New) The cryptographic module of Claim 36 wherein said host network processor formats the data portions based upon the simple network management protocol (SNMP).

38. (New) The cryptographic module of Claim 36 wherein the communications module command packets comprise Ethernet packets.

39. (New) The cryptographic module of Claim 36 wherein the cryptographic processor command packets comprise Internet protocol (IP) packets.

40. (New) The cryptographic module of Claim 36 wherein said cryptographic processor comprises:

In re Patent Application of:

YANCY ET AL.

Serial No. 10/806,948

Filing Date: **March 23, 2004**

_____/

an unencrypted data buffer circuit coupled to said host network processor;

a cryptography circuit coupled to said unencrypted data buffer circuit; and

an encrypted data buffer circuit coupled to said cryptography circuit.

41. (New) The cryptographic module of Claim 36 wherein said user network interface comprises an Ethernet Local Area Network (LAN) interface.